

Tiefen der Abstandsflächen:

T1=	0.2x (95.56-88.15)	= 3.00m
T2=	0.2x (98.46-88.15)	= 3.00m
T3=	0.2x (98.46-88.06)	= 3.00m
T4=	0.2x (95.86-88.06)	= 3.00m
T5=	0.2x (95.56-88.06)	= 3.00m
T6=	0.2x (97.45-88.06)	= 3.00m
T7=	0.2x (98.46-88.07)	= 3.00m
T8=	0.2x (95.56-88.07)	= 3.00m
T9=	0.2x (97.45-88.07)	= 3.00m
T10=	0.2x (95.56-88.09)	= 3.00m
T11=	0.2x (98.46-88.09)	= 3.00m
T12=	0.2x (97.45-88.09)	= 3.00m

Grund- und Geschossflächenberechnung:

Grundfläche der Hauptanlagen:

Halle (EG in Bau)	= 478qm
Büro/Lagerhalle (EG Bestand)	= 225qm
Büro/Lagerhalle (OG Bestand)	= 225qm
Büro/Ausstellung/BLW (EG Neu)	= 153qm
Büro/Ausstellung/BLW (1.OG Neu)	= 175qm
Büro/Ausstellung/BLW (2.OG Neu)	= 161qm

Summe der Hauptanlagen GRZ	= 856m
Summe der Hauptanlagen GFZ	= 1417m

GE	III
0.8	(2.0)
Z 4	

